

Performance Plus Treadmill

PREMIUM LED CONSOLE T-PP-PLED

Our exceptional treadmill sets a new standard with a shock-absorbing slat-belt and a powerful drive system that make even the most intense runs feel comfortable, solid and smooth, lasting up to 100,000 miles in the most intense environments. Despite this incredible evolution of technology, service and maintenance have never been easier.



Give members the intuitive navigation of an LED with a more engaging look. An 8,000-pixel display fills the screen with color and sharp graphics, providing clear, easy-to-read feedback in large numbers and letters.

CONSOLE	
DISPLAY	8,000-pixel multi-color LED
WORKOUTS	Go, manual, Sprint 8†, Landmarks†, target heart rate, interval training, fat burn, rolling hills, constant watts†, glute training†, 5k/10k, fitness tests †Some of these programs may not be available on this frame.
LANGUAGES	English, German, French, Italian, Spanish, Dutch, Portuguese, Swedish, Finnish, Turkish, Danish, Polish
IFIT ON-DEMAND WORKOUTS	No
FAN	Yes
ANALOG TV	Optional; attachable add-on TV
DIGITAL TV	Optional; attachable add-on TV
IPTV	No
PRO:IDIOM COMPATIBILITY	Optional; attachable add-on Pro:Idiom TV (≠ IPTV)
WIFI	Yes
BLUETOOTH	Yes; heart rate
ANT+	No
RFID WIRELESS LOGIN	Optional
CONNECTS TO APPLE WATCH	Optional
MADE FOR IPHONE®, IPAD®, IPOD®	No
USB PORT	Yes; device charging, software updates
CONNECTS TO SAMSUNG GALAXY WATCH	No
WIRELESS CHARGING (QI)	No

CSAFE READY	Yes
AUTO WAKE-UP	No
FRAME	
TREAD SENSE	Yes
SPEED RANGE	0.8–26 km/h / 0.5–16 mph
STEP-ON HEIGHT	25 cm / 10.5"
RUNNING SURFACE TYPE	Slat belt
SERVICE CASTER	Yes
MAX USER WEIGHT	227 kg / 500 lbs.
POWER REQUIREMENTS	20 A dedicated circuit required, non-looped grounded
RUNNING SURFACE AREA	157 x 61 cm / 62" x 24"
ASSEMBLED DIMENSIONS	227 x 92.6 x 168.9 cm / 89.4" x 36.5" x 66.5"
CAST ALUMINUM END CAPS	Yes
CONTACT & TELEMETRIC HR	Yes
CROSSBAR CONTROLS	Yes
CUSHIONING SYSTEM	Pure Stride
DRIVE SYSTEM	5.0 hp Dynamic Response Drive System
ETHERNET CONNECTIVITY	Yes
HANDLEBAR DESIGN	Continuous multi-grip design
INCLINE RANGE	0–20% (1,650-lb. thrust-elevation motor)
ASSEMBLED WEIGHT	217.6 kg / 479.7 lbs.
SHIPPING WEIGHT	244.4 kg / 538.8 lbs.